

ARTICLE NR. : S204140010002

Technical points and tolerances

Name	alu-deksel Cat.Deksel 0.25 RPET helder	
Material / Color	RPET dry	CLEAR
Thickness (mm)	0,25	+/-10%
Length (mm)	204	
Width (mm)	140	
Depth (mm)	10	
Weigth (gr)/ piece	9	+/-10%
Compartiments	1	
Temp (°C)	-20 °C/+65 °C	

Special demands

Food approval

Production at Proplastics BVBA uses only raw materials regarding which our suppliers have declared conformity with the provision of the EU Directive EC 2002/72 and EC10/2011 (rules governing the monomers and other basic materials that may be used in the production of raw materials for plastics intended to come into contact with foods).

These raw materials also conform to EU directive EEC 94/62 dealing with heavy metals.

Packaging

- Each box is provided with date of production and batch No. for traceability
- The number of trays per carton may vary +/- 4%. However this should be equalised over the total order
- All pallets are wrapped and efficiently protected
- Packaging:

Pieces / box : 500

Boxes / pallet : 20

All statements or recommendations are based on data and knowledge considered to be true and accurate at the time of printing but should be verified by the user. Since the conditions of use are beyond our control we do not warrant the completeness or suitability for any intended purpose of any statement or recommendation, or the result to be obtained. National or local legal requirements to health & safety at work and the protection of the environment shall be applicable in all cases. Our products or not suitable for babyfood.

P.S. Technical information can not be used for making sealing equipment and developing automatic production lines. Therefore a detailed drawing can be obtained at Proplastics.